

# Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

## Valvoline DuraBlend motor oil

002/09

Valvoline DuraBlend motor oil is formulated with a combination of synthetic and premium quality base oils and advanced additive technology. This motor oil helps engines maintain peak performance by providing protection under severe service conditions. DuraBlend motor oil meets the performance requirements of virtually all cars and light trucks (vans), including gasoline, diesel, and LPG engines. In the special VW DID test for direct injected diesel engines the new formulation DuraBlend performs very well with regards to piston cleanliness and ring sticking.

### The Valvoline DuraBlend motor oil advantages

- \* **Deposit Control** : Improved piston cleanliness prevents ring sticking.
- \* **Stay in grade** : Keeps its protective oil film during the whole refreshment period
- \* **Cold start** : Easy Oil Flow at low temperatures
- \* **Wear Protection**: Improved oil film strength and breakdown resistance

Approvals/Performance levels	viscosity grade
API SL/CF	10W-40
ACEA A3/B4-04	10W-40
Mercedes-Benz 229.1	10W-40
Renault RN0700	10W-40
VW 501.01 (2005-03)	10W-40
VW 505.00 (1/97)	10W-40

Typical Properties	10W-40
Viscosity, mm <sup>2</sup> /s @ 100 °C	14.1
Viscosity, mm <sup>2</sup> /s @ 40 °C	95
Viscosity Index	152
Viscosity, mPa.s -25 °C	<7000
Sulphated Ash, wt. %	1.3
TAN; mg KOH/g (ASTM D-664)	1.5
TBN; mg KOH/g (ASTM D-2896)	10.1
Pour Point, °C	-36
Specific Gravity @ 15/15°C	0.879
Flash Point, COC, °C	225

This information only applies to products manufactured in the following location(s): Europe.

Effective Date:                      Replaces:                      Author's Initials:                      Code:  
Sept. 2007                              002/08                              AdG

*The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.*