

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Unitrac

703/07

Valvoline Unitrac is a premium multi-purpose fluid designed for year-round service in tractor hydraulic systems, transmissions, and differentials with wet brake systems. The product is not designed for use as an engine lubricant. Valvoline Unitrac protects against wear and corrosion of tractor components and has excellent friction properties.

Recommended for use where the following specs are specified	Viscosity Grade
API GL-4+	80W
Ford M2C-134 A/B/C/D, M2C 86B/C, M2C-43	80W
Ford/NewHolland A2C-200/A, 201	80W
Fiat-Hesson Multi-F/G	80W
MasseyFerguson M-1135, M-1141, M-1143, M-1145	80W
John Deere J20 A/B/C, J14B/C, J21A	80W
Case MS 1205/6/7/9	80W
Kubota UDT	80W
Komatsu	80W
Steiger SEMS 17001	80W
Versatile 23M, 24M	80W
Volvo VME, VCE WB 101	80W
White Farm Q-1826	80W
Allison C3, C4	80W
ZF TE-ML 03E, 05F, 06K, 17E	80W

Typical Properties	80W
Viscosity, mm ² /s @ 100 °C	10.0
Viscosity, mm ² /s @ 40 °C	63.7
Viscosity Index	141
Sulphated Ash, wt. %	1.41
TAN; mg KOH/g (ASTM D-664)	2.0
TBN; mg KOH/g (ASTM D-2896)	9.0
Pour Point, °C	-36
Specific Gravity @ 15/15°C	0.886
Flash Point, COC, °C	220

This information only applies to products manufactured in the following location(s): Europe

Effective Date: 05-05-2008 Replaces: 703/06 Author's Initials: AdG

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.