

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



SynPower™ 2T

301/05

SynPower 2T is a high performance fully synthetic low-smoke motor oil for all 2-cycle motorcycle engines. The product is specially formulated to exceed the requirements of all leading motorcycle manufacturers and provides superior protection in severe operating extremes. SynPower 2T gives a strong oil film that protects against wear and corrosion. The product is pre-diluted for easier mixing and may be used in both injector and pre-mix applications. Use fuel/oil ratios as specified by the engine manufacturer up to a maximum of 100:1.

Approvals/performance levels	Viscosity Grade
API TC	
Jaso FD	
ISO L-EGD	

Typical Properties	
Viscosity, mm ² /s @ 100 °C	10.0
Viscosity, mm ² /s @ 40 °C	60
Viscosity Index	162
Sulphated Ash, wt. %	0.15
TBN; mg KOH/g (ASTM D-2896)	2.2
Pour Point, °C	-51
Specific Gravity @ 15/15°C	0.873
Flash Point, PMCC, °C	80

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
30-8-2010	301/04	AdG	

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2010, Ashland

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.

ASHLAND