

# Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

## DuraBlend™ 2T

302/04

DuraBlend 2T is a high performance synthetic blend low-smoke motor oil for all 2-cycle motorcycle engines. Specially formulated to meet the requirements of all leading motorcycle manufacturers. DuraBlend 2T provides optimum performance, helps keep the engine clean, and prevents scuffing and ringsticking. The product is pre-diluted for easier mixing and may be used for both injector and pre-mix applications. Use fuel/oil ratios as specified by the engine manufacturer up to a maximum of 100:1.

Approvals/performance levels	Viscosity Grade
API TC	
JASO FD	
ISO L-EGD	

Typical Properties	
Viscosity, mm <sup>2</sup> /s @ 100 °C	9.4
Viscosity, mm <sup>2</sup> /s @ 40 °C	60
Viscosity Index	140
Sulphated Ash, wt. %	0.12
TBN; mg KOH/g (ASTM D-2896)	3.1
Pour Point, °C	-42
Specific Gravity @ 15/15°C	0.868
Flash Point, PMCC, °C	90

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
16-8-2010	302/04	AdG	

\*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2010, Ashland

*The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.*