

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline Racing Oil 2T (fully synthetic)

311/04

Valvoline Racing Oil 2T is a fully synthetic 2-stroke oil for water cooled motorcycle racing engines. The product is specially developed and tested to meet the most severe racing circumstances. Used in rainy weather, the product will not cause any throttle sticking. Valvoline Racing Oil 2T is non-prediluted and can not be used in oil-injection systems. Do not mix with other lubricants.

| Approvals/performance levels | | Viscosity Grade |
|------------------------------|----|-----------------|
| SAE | 50 | |

| Typical Properties | 50 |
|----------------------------------------|-------|
| Viscosity, mm ² /s @ 100 °C | 18.0 |
| Viscosity, mm ² /s @ 40 °C | 145 |
| Viscosity Index | 125 |
| TBN; mg KOH/g (ASTM D-2896) | 3.85 |
| Pour Point, °C | -36 |
| Specific Gravity @ 15/15°C | 0.920 |
| Flash Point, PMCC, °C | 226 |

This information only applies to products manufactured in the following location(s): Europe

| | | | |
|-----------------|-----------|--------------------|------|
| Effective Date: | Replaces: | Author's Initials: | Code |
| March 4, 2005 | 311/03 | AdG | |

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.