

# Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



## Valvoline™ Motorcycle Oil 2T

305/03

Valvoline Motorcycle Oil 2T is a premium 2-cycle motorcycle engine oil for use in both oil injection and pre-mix systems. The product is formulated to reduce smoke, and is ideal for smaller and older motorcycle engines. Valvoline Motorcycle Oil 2T prevents spark plug fouling and carbon deposits and helps keep the engine clean. This oil is pre-diluted for easier mixing and may be used for both injector and pre-mix applications. Use fuel/oil ratios as specified by the engine manufacturer up to a maximum of 50:1.

Approvals/performance levels	Viscosity Grade
API TC	
JASO FB	
ISO L-EGB	

Typical Properties	
Viscosity, mm <sup>2</sup> /s @ 100 °C	9.2
Viscosity, mm <sup>2</sup> /s @ 40 °C	65
Viscosity Index	118
Sulphated Ash, wt. %	0.05
TBN; mg KOH/g (ASTM D-2896)	1.2
Pour Point, °C	-36
Specific Gravity @ 15/15°C	0.874
Flash Point, PMCC, °C	96

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
30-8-2010	305/02	AdG	

\*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2010, Ashland

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.

**ASHLAND**