Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

SynPower[™] 4T 306/04

SynPower 4T is a high performance fully synthetic motor oil for all 4-cycle motorcycle engines. The product is wet clutch compatible and is recommended for Japanese and other motorcycles where API SG or JASO MA fluids are specified. This product is specially formulated to exceed the requirements of all leading engine manufacturers and provides superior protection in severe operating conditions. SynPower 4T gives a quick cold start and smooth lubrication, even under very cold weather circumstances.

Approvals/performance levels		Viscosity Grade	
API SG	10W40		
JASO MA	10W40		

Typical Properties	10W40
Viscosity, mm ² /s @ 100 °C	14.7
Viscosity, mm ² /s @ 40 °C	91
Viscosity Index	169
Viscosity, mPa.s -25°C	<7000
Sulphated Ash, wt. %	0.82
TAN; mg KOH/g (ASTM D-664)	2.50
TBN; mg KOH/g (ASTM D-2896)	6.20
Pour Point, °C	-42
Specific Gravity @ 15/15°C	0.848
Flash Point, COC, °C	230

This information only applies to products manufactured in the following location(s): Europe

Effective Date: Replaces: Author's Initials: Code 27-8-2010 306/03 AdG

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.



^{*}Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2010, Ashland