

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

DuraBlend™ 4T

307/03

Durablend 4T is a high performance synthetic blend motor oil for all 4-cycle motorcycle engines. The product is wet-clutch compatible and is recommended for Japanese and other motorcycles where an API SG or JASO MA fluid is specified. The product is specially formulated to meet the requirements of all leading motorcycle manufacturers and to protect under severe operating conditions. The select high quality base stocks and the finest extreme pressure additives provide optimum film strength. The viscosity SAE 10W-40 is recommended for quick cold starting.

Approvals/performance levels	Viscosity Grade	
API SG	10W40	20W50
JASO MA	10W40	20W50

Typical Properties	10W40	20W50
Viscosity, mm ² /s @ 100 °C	14.5	18.2
Viscosity, mm ² /s @ 40 °C	97	159
Viscosity Index	155	127
Viscosity mPa.s -25°C.	<7000	
Viscosity, mPa.s -15 °C		<9500
Sulphated Ash, wt. %	0.82	0.82
TAN; mg KOH/g (ASTM D-664)	2.50	2.50
TBN; mg KOH/g (ASTM D-2896)	6.20	6.20
Pour Point, °C	-39	-27
Specific Gravity @ 15/15°C	0.870	0.883
Flash Point, COC, °C	210	224

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
16-8-2010	307/02	AdG	

*Trademark owned by a third party™ Trademark of Ashland or its subsidiaries, registered in various countries © 2010, Ashland

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.