

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

DuraBlend™ Gear Oil GL-5

205/05

DuraBlend Gear Oil GL-5 is a high performance synthetic blend gear oil specially formulated to provide enhanced protection, lubrication and easier shifting over a wide temperature range. For use in all (hypoid) transmissions and transaxles where a API GL-5 gear oil is specified by the manufacturer. DuraBlend Gear Oil GL-5 protects against rust and corrosion and provides an excellent lubrication under hot and very cold weather conditions. Not recommended for limited slip applications.

Approvals/Performance levels	Viscosity Grade
API GL-5	75W90
MIL-L-2105D	75W90

Typical Properties	75W90
Viscosity, mm ² /s @ 100 °C	16.9
Viscosity, mm ² /s @ 100°C. after shearing (CEC: L-45-T-93)	stay-in-grade
Viscosity, mm ² /s @ 40 °C	107
Viscosity Index	172
Viscosity, mPa.s -40 °C	<150.000
TAN; mg KOH/g (ASTM D-664)	2.1
Pour Point, °C	-42
Specific Gravity @ 15/15°C	0.873
Flash Point, COC, °C	>210

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
20-8-2010	205/04	AdG	

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2010, Ashland

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.